



PULSAR
INDUSTRIES

**REDEFINING ENERGY
INDEPENDENCE**

LIBERI

POWER THAT ADAPTS. ENERGY **THAT LASTS**



LIBERI



LEVEL II IDEAL FOR:



Pulsar Industries, 2025 ALL RIGHTS RESERVED

www.pulsar.industries | info@pulsar.industries | [info@pulsar.industries](https://www.linkedin.com/company/pulsar-industries)



TECHNICAL SPECIFICATION

MODEL NAME	SE-1331V-3.3M	SE-1331V-5M	SE-1331V-6.7M	SE-1331V-8.3M
BATTERY SYSTEM PARAMETER				
Battery capacity	9P416S	12P416S	15P416S	20P416S
Charge/discharge rate	280Ah	314Ah	280Ah	300Ah
System rated capacity	0.5C	0.5C	0.5C	0.5C
Rated energy	2520Ah	3768Ah	5040Ah	4500Ah
Rated voltage	3.3MWh	5MWh	6.7MWh	8.3MWh
Voltage range	1331.2V	1331.2V	1331.2V	1331.2V
GENERAL PARAMETER				
Operation temperature Discharge	20~55°C/Charge: 0~55°C			
Communication	RS485, CAN, Ethernet			
GENERAL PARAMETER				
Protection Degree	IP54	IP54	IP54	IP54
Size	20FT	20FT	40FT	40FT
Cooling system	Liquid cooling	Liquid cooling	Liquid cooling	Liquid cooling
Fire fighting system	Aerosol	Aerosol	Aerosol	Aerosol